



BIOS SETUP UTILITY

Advanced

IDE Configuration

ATA/IDE Configuration [Enhanced]
 Configure SATA as [IDE]
 Configure SATA Channels [Before PATA]
 Port3 SATA AHCI Speed: GEN 2 (3.0 Gb/sec)

▶ Primary IDE Master : [Not Detected]
 ▶ Primary IDE Slave : [Not Detected]
 ▶ Secondary IDE Master : [Not Detected]
 ▶ Secondary IDE Slave : [Hard Disk]
 ▶ Third IDE Master : [Not Detected]
 ▶ Third IDE Slave : [Not Detected]

Hard Disk Write Protect [Disabled]
 IDE Detect Time Out (Sec) [35]
 ATA(PID) 80Pin Cable Detection [Host & Device]
 Staggered Spin-up delay [Disabled]

Options

Disabled
Compatible
Enhanced

+ Select Screen
 ↑↓ Select Item
 +- Change Option
 F1 General Help
 F10 Save and Exit
 ESC Exit

v02.59+ (C) Copyright 1985-2005, American Megatrends, Inc.



DEWE-1201

Advanced

LAN Configuration

ETH1 Configuration [Enabled]
 MAC Address : 00E0F41E8F2B -

ETH2 Configuration (Upper) [Enabled]
 MAC Address : 00E0F41E8F2C -

ETH3 Configuration (Lower) [Enabled]
 MAC Address : 00E0F41E8F2D -

Control of Ethernet
Devices and PXE boot

+ Select Screen
 ↑↓ Select Item
 +- Change Option
 F1 General Help
 F10 Save and Exit
 ESC Exit

v02.59+ (C) Copyright 1985-2005, American Megatrends, Inc.



DEWE-1201















