
Anritsu GROUP COMPANY

DEWETRON

CERTIFIED CMMC 2.0 LEVEL 2








PRODUCT GUIDE








WE ARE PASSIONATE ABOUT WHAT WE DO






We love what we do. You can see that in the quality of our test and measurement systems and in the satisfaction of our customers.


"You are always solution-oriented and always try to help us somehow, even if there is sometimes no technical solution."
- Framatome -

"Thank you very much for supporting us in such a way that we can serve our projects, despite the difficulties in procurement, which I can understand. I am very glad that I chose DEWETRON."
- Siemens Amberg -

"With the old software, I had to do a lot of trickery; that's not necessary with OXYGEN. Well thought out from start to finish."
- IABG -



We know that your developments depend on the reliability and accuracy of our measurement systems and therefore they have top priority. We work to the highest quality standards and guarantee you reliable and highly precise measurement data since 1989. We stand for Austrian quality.




THE MEASURABLE DIFFERENCE.

Scan to download this Product Guide

CONTENTS

PORTFOLIO & SERVICES 4
HIGHEST QUALITY 6
SYSTEM OVERVIEW 7
TRION & TRION3 MODULES 8
ANALOG OUTPUT 10
POWER ANALYSIS 12
LITE[PA] 14
TEST STAND INTEGRATION 15
ALL-IN-ONE SYSTEMS 16
MAINFRAME SYSTEMS 17
RACK-MOUNT MAINFRAMES 18
TRIONet3 FRONT-END 19
RUGGED & COMPACT: NEX[DAQ] 20
PURE RECORDING: PU[REC] 21
RUGGED CHANNEL EXPANSIONS: XR 22
MSI SENSOR ADAPTER 23
SYNCHRONIZATION 24
ANALOG SIGNAL CONDITIONING 26
OXYGEN MEASUREMENT SOFTWARE 27
SDK FOR PROGRAMMERS 33
LABVIEW™ INTEGRATION 35
CUSTOMER CARE CENTER 36
ELECTRICAL POWER & NVH 38
ACCESSORIES 39









PORTFOLIO & SERVICES

RELIABLE and PRECISE measurement data play an essential role in your daily business? The requirements in your CHALLENGING test and measurement tasks change frequently and you need to be very FLEXIBLE? The DAQ hardware and even the used software should be CUSTOMIZABLE and EASY TO USE?

We listen to our customers and offer MODULAR DAQ SOLUTIONS – you have the choice.

CONFIGURE YOUR INDIVIDUAL DAQ SOLUTION

CHASSIS + **MODULES** + **SOFTWARE** =



DEWE3

DIFFERENT CHASSIS LIKE ALL-IN-ONE WITH DISPLAY, FRONT-END, 19″ RACK-MOUNT...



TRION(3)

USER-EXCHANGEABLE TRION(3) MODULES FOR ALL INPUT SIGNALS; UP TO 10 MS/S




OXYGEN

OXYGEN MEASUREMENT SOFTWARE: POWER ANALYSIS, ORDER ANALYSIS, FFT...

MEASUREMENT CHAIN OF ANALOG SIGNALS

TRION(3) modules are the heart of every DEWETRON measurement system. The sensing of physical parameters such as vibrations, strains, noise, pressure, force, current etc. is usually carried out with sensors that output analog signals. TRION(3) modules take over the precise signal conditioning, digitization and filtering of these signals and make the data available for further processing and storage.



In addition, TRION(3) modules provide strong and stable sensor excitation and various types of industrial connectors, making it easy to connect every sensor!

YOUR **DAQ SYSTEM**



FOR EXAMPLE: DEWE3-A4, DEWE3-PA8 POWER ANALYZER, DEWE3-A4L, TRIONet3, DEWE3-M4, DEWE3-RM16, DEWE3-PA8-RM

CUSTOMER CARE CENTER


- CALIBRATION (ISO 17025)
- FIRST LEVEL SUPPORT
- SYSTEM UPGRADE
- SECOND LEVEL SUPPORT
- 5-YEAR WARRANTY EXTENSION
- DEWETRON TRAINING ACADEMY
- REPAIR
- MAINTENANCE
- RENTAL SERVICE

PROCESSED SIGNALS IN 100 % SYNC

- VOLTAGE
- CURRENT
- POWER
- THERMO-COUPLE
- POTENTIO-METER
- RTD
- IEPE© (VIBRATION)
- BRIDGE
- CHARGE
- COUNTER
- VIDEO
- SOUND
- GPS SYNC
- IRIG SYNC
- PTP SYNC
- PPS SYNC
- IMU
- SENSOR ADAPTER
- DIGITAL INPUT
- DIGITAL I/O
- ANALOG OUTPUT
- LVDT
- CAN-BUS
- CAN-BUS
- SCPI
- XCP
- ETHERCAT
- FLEXRAY
- ARINC-BUS
- MIL-BUS

HIGHEST QUALITY
MADE IN AUSTRIA

Our commitment to Total Quality Management is based on understanding what is important for the success of our customers. It starts with the definition of the technical specification, covers development, production, quality control, shipment and ends with support and service of our systems during operation. All DEWETRON products go through a tough product qualification phase before being approved for the market. With our quality control methods, we can assure you the highest reliability so that the products fulfill their function over a long period of time.



RADIATED IMMUNITY

We test the immunity of our devices against radiated disturbances by using a generator and an antenna to create a strong modulated, electromagnetic field. Testing is conducted in a special anechoic test chamber in a certified contract lab.



OPERATING & STORING TEMPERATURE, HUMIDITY

We use climate chambers to validate our environmental specifications (e.g. temperature ranges of -40 to +70 °C). So we can ensure, that our DEWETRON products can be used on a Swedish ice lake as well as in Nevada's desert.




ESD IMMUNITY (ELECTROSTATIC DISCHARGE)

If an electrostatically charged object touches a conductive part of a device, an unwanted, sudden flow of electricity is induced, which can destroy electrical circuits. We simulate this with our ESD (electrostatic discharge) gun.




THERMAL TESTING

We use thermal testing to detect any potential hotspot, component failures during operation, or other issues that could lead to unexpected performance.



MECHANICAL & SEISMIC SHOCK, VIBRATION


We test all of our devices on electrodynamic shakers to simulate vibrations and impacts during operation and transport.



BURST/SURGE IMMUNITY, VOLTAGE DIPS

We simulate voltage dips, power interruptions, surge and burst phenomena during our product qualification tests using special generators.

SYSTEM OVERVIEW



POWER ANALYZER

> Up to 16 power phases
> 0.03 % measurement error (1 to 1000 Hz)
> Additional, mixed signals
> Integrated redundant current transducer supply

Consisting of these parts:





ALL-IN-ONE SYSTEMS

> Built-in display
> Compact and flexible configuration
> Powerful PC inside for fast online displays and analysis
> Battery power option

Consisting of these parts:





MAINFRAME SYSTEMS

> Powerful PC inside for fast online displays and analysis
> Can be used with external monitor
> The ideal solution for installations in a 19" rack

Consisting of these parts:






FRONT-END SYSTEMS

> Used with an external computer
> Ideal for small channel count application
> Fully synchronized expansion for all-in-one or mainframes
> Multiple units can be daisy-chained
> Connected via USB3.0 or GBit-Ethernet

Consisting of these parts:





DATA LOGGER NEX[DAQ]

> Used with an external computer
> Rugged & compact data logger
> IP67 rating
> 8 measurement channels
> Channel count expandable via XR modules or MSI sensor adapter

Consisting of these parts:





SIGNAL CONDITIONING

> Stand-alone analog signal conditioning
> Front-ends for existing recorders, A/D boards ...
> Up to 300 kHz bandwidth

Consisting of these parts:





TRION & TRION3 MODULES

Choose from our various TRION(3) signal conditioning modules to measure analog signals from any sensor absolute synchronously. Enjoy maximum flexibility with these user-exchangeable modules featuring A/D conversion on each channel and anti-aliasing filters.

ANALOG MODULES	CHANNELS	SAMPLE RATE PER CHANNEL	RESOLUTION	ISOLATION	CONNECTOR TYPES
TRION3-1850-MULTI [1] TRION3-1820-MULTI [1] NEW TRION3-1802-MULTI [1]	4 or 8	1850: 5 MS/s 1820: 2 MS/s 1802: 200 kS/s	24-bit >2 MS/s: 18-bit	yes	4 D-SUB or 8 LEMO 0B
TRION-2402-MULTI	8	200 kS/s	24-bit	yes	8 LEMO 0B
TRION3-1810-HV [1] [2]	4 to 8	1 MS/s	24-bit	yes	4 x Safety banana, 4x depend. on sub-modules
TRION3-1810-SUB-8 [1] [2] [3] Carrier board for up to 8 sub-modules	8	1 MS/s	Depending on 8 x sub-modules		
TRION3-1810M-SUB-8 [1] [2] [3] Carrier board for up to 8 sub-modules	8	10 MS/s	Depending on 8 x sub-modules		
TRION-2402-dSTG	8	200 kS/s	24-bit	no	8 LEMO 0B, 8 RJ45
NEW TRION3-2402-ACC [1]	6	200 kS/s	24-bit	yes	6 BNC
NEW TRION3-2402-LV [1]	6	200 kS/s	24-bit	yes	6 BNC
NEW TRION3-2420-ACC [1]	6	2 MS/s	24-bit	yes	6 BNC
NEW TRION3-2420-LV [1]	6	2 MS/s	24-bit	yes	6 BNC
TRION3-1802-dLV [1]	16 or 32	200 kS/s 100 kS/s	18-bit 24-bit	no	D-SUB
TRION3-1600-dLV [1]	16 or 32	20 kS/s	16-bit	no	D-SUB

Inputs depending on used sub-modules

[1] All TRION3 modules require a DEWE3 chassis

[2] These modules occupy 2 TRION(3) slots

[3] Max. sample rate limit, also depending on sub-modules (see page 13)

PLEASE FIND THE ICON EXPLANATION ON PAGE 5

DIGITAL MODULES	CHANNELS	SAMPLE RATE PER CHANNEL	ISOLATION	FEATURES
TRION-CNT	6	2 MS/s	yes	6 advanced counter
TRION-DI-48	48	3 MS/s	yes	48 high-speed digital IN
TRION-BASE	-	2 MS/s	no	Basic IO card with simple IRIG sync and 2 counter
TRION-VGPS-V3	-	2 MS/s	no	100 Hz GNSS receiver for automotive applications
TRION-TIMING-V3	-	2 MS/s	no	Applies precision absolute time to measured data
TRION3-CAN-FD [1]	4	Up to 8 MBit	yes	D-SUB
TRION-ARINC429	4 or 16	-	no	Decoding of ARINC 429, export of decoded signals
TRION-MIL1553	1 or 4	-	no	Decoding of MIL-STD-1553, export of decoded signals
TRION-EtherCAT-1-SLAVE	100	500 S/s	yes	Measurement data output
NEW TRION-PROFINET-IO-DEVICE	100	500 S/s	yes	Measurement data output

[1] All TRION3 modules require a DEWE3 chassis

POWER MODULES	CHANNELS	SAMPLE RATE PER CHANNEL	RESOLUTION	ISOLATION	CONNECTOR TYPES
TRION3-1810M-POWER [1] [2]	8 (4 U / 4 I)	10 MS/s	18-bit	yes	4 x Safety banana, 4x depend. on sub-modules
TRION3-1820-POWER [1] [2]	8 (4 U / 4 I)	2 MS/s	18-bit	yes	4 x Safety banana, 4x depend. on sub-modules
TRION3-1810-HV [1] [2]	8 (4 U / 4 I)	1 MS/s	24-bit	yes	4 x Safety banana, 4x depend. on sub-modules
TRION3-1810-SUB-8 [1] [2] [3] Carrier board for up to 8 sub-modules	8	1 MS/s	Depending on 8 x sub-modules		
TRION3-1810M-SUB-8 [1] [2] [3] Carrier board for up to 8 sub-modules	8	10 MS/s	Depending on 8 x sub-modules		

Inputs depending on used sub-modules

[1] All TRION3 modules require a DEWE3 chassis [2] These modules occupy 2 TRION(3) slots [3] Max. sample rate limit, also depending on sub-modules (see page 13)

ANALOG OUTPUT MODULES	CHANNELS	SAMPLE RATE PER CHANNEL	RESOLUTION	ISOLATION	CONNECTOR TYPES
TRION3-1850-MULTI-AOUT [1] [2]	IN: 8 OUT: 8	IN: 5 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: LEMO 0B OUT: D-SUB, BNC
TRION3-1820-MULTI-AOUT [1] [2]	IN: 8 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: LEMO 0B OUT: D-SUB, BNC
NEW TRION3-2420-ACC-AOUT [1] [2]	IN: 6 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: BNC OUT: D-SUB, BNC
NEW TRION3-2420-LV-AOUT [1] [2]	IN: 6 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: BNC OUT: D-SUB, BNC
TRION3-AOUT [1]	OUT: 8	OUT: 2.5 MS/s	OUT: 16-bit or 32-bit	OUT: yes	OUT: D-SUB, BNC

[1] All TRION3 modules require a DEWE3 chassis [2] These modules occupy 2 TRION(3) slots

MAXIMUM FLEXIBILITY WITH PLUG&PLAY TRION(3) MODULES

You are absolutely flexible with the user-exchangeable TRION(3) modules: Choose your suitable TRION(3) modules, plug them into your DEWE3 DAQ system, turn the system on and get to work. The modules are automatically identified and configured within the software as soon as it is launched.



PLEASE FIND THE SIGNAL ICON EXPLANATION ON PAGE 5

PLEASE FIND THE SIGNAL ICON EXPLANATION ON PAGE 5

ANALOG OUTPUT


The TRION3-x-AOUT modules offer several ways to output analog signals for different use cases such as signal conditioning, waveform generation or playback of recorded data. In particular, true 3-way isolation, bandwidth of up to 600 kHz for the analog output and the industry-leading dynamics, which is achieved by 32-bit D/A-converters, must be emphasized.

32-bit D/A converter

UNIVERSAL **SIGNAL CONDITIONING & PROCESSING**

ANALOG INPUT SIGNALS

- VOLTAGE
- CURRENT
- IEPE© (VIBRATION)
- BRIDGE
- RTD
- POTENTIOMETER
- COUNTER INPUTS
- CAN-BUS



ISOLATED CONDITIONED OUTPUT SIGNALS

OUTPUT SIGNALS

±5 V (e.g. 2 mV/V ≙ ±5 V)
±10 V
0 - 5 V
0 - 10 V
±30 mA
0 - 30 mA

REAL-TIME SIGNAL PROCESSING

> Actual value
> Average
> RMS
> MATH (A+B, A-B, AxB)

SIGNAL GENERATION

> Constant output
  > Voltage up to ±10 V
  > Current up to ±30 mA
> Stream output
  > Replay recorded data
  > Live stream output
> Function generator (sine, square, triangle, custom pattern)

TRION3-18XX-MULTI-AOUT-8 MODULES

These universal signal conditioning & processing modules are typically used when it comes to mission-critical applications in which the sensor data must be stored redundantly.
In these cases, after conditioning, digitization and filtering of the analog signals, the data is sent to the DEWE3 system's CPU via the PXIe interface as usual but additionally made available in parallel as analog signals for a second digitization system. Since the signal processing and the analog output run independently, the measurement data is available to the redundant system at all times, even if there is a problem in the main system.

ADDITIONAL FUNCTIONS

To make things even better, onboard real-time data processing is available, so the analog output can represent not only the actual input value, but also average or RMS values. Simple calculations such as addition, subtraction or multiplication of channel data are also possible. All channels and values can be freely assigned to the available output connectors.
Of course, these modules can also be used for signal generation or to replay recorded data files, see details at TRION3-AOUT-8.

ANALOG OUTPUT MODULES	CHANNELS	SAMPLE RATE PER CHANNEL	RESOLUTION	ISOLATION	CONNECTOR TYPES
TRION3-1850-MULTI-AOUT [1) 2)]	IN: 8 OUT: 8	IN: 5 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: LEMO 0B OUT: D-SUB, BNC
TRION3-1820-MULTI-AOUT [1) 2)]	IN: 8 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: LEMO 0B OUT: D-SUB, BNC
NEW TRION3-2420-ACC-AOUT-6 [1) 2)]	IN: 6 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: BNC OUT: D-SUB, BNC
NEW TRION3-2420-LV-AOUT-6 [1) 2)]	IN: 6 OUT: 8	IN: 2 MS/s OUT: 2.5 MS/s	IN: 24-bit OUT: 16-bit or 32-bit	IN: yes OUT: yes	IN: BNC OUT: D-SUB, BNC
TRION3-AOUT-8 [1)]	OUT: 8	OUT: 2.5 MS/s	OUT: 16-bit or 32-bit	OUT: yes	OUT: D-SUB, BNC

[1)] All TRION3 modules require a DEWE3 chassis
[2)] These modules occupy 2 TRION(3) slots


POWERFUL **SIGNAL GENERATION**

ARBITRARY WAVEFORM



SIGNAL GENERATION

> Constant output
  > Voltage up to ±10 V
  > Current up to ±30 mA
> Stream output
  > Replay recorded data
  > Live stream output
> Function generator (sine, square, triangle, custom pattern)



TRION3-AOUT-8 MODULES

The TRION3-AOUT-8 modules are very powerful signal generation modules. Each module provides 8 isolated output channels for voltage (±5 V, ±10 V) or current (±30 mA) signals. The simplest application is the output of constant signals as default values or for simple control processes.

The FPGA based arbitrary waveform generator not only supports the generation of sine, square or triangle signals but also enables users to load their own custom patterns. The so called "stream output" mode enables the replay of recorded data channels as analog signals during a measurement. This simplifies reference curve generation during a measurement significantly.

DAC MODES

Set the high-speed or high-resolution mode individually for every channel.

DAC MODE	HIGH-SPEED	HIGH-RESOLUTION
UPDATE RATE	2.5 MS/s	500 kS/s
DAC RESOLUTION	16-bit	32-bit
LATENCY	<5 µs	<100 µs
BANDWIDTH	600 kHz	70 kHz

ADVANCED POWER ANALYSIS

Build the power analyzer you need with our dedicated power modules.
The perfect advanced power analyzer for every field of application.


> Modular high-precision tailormade power analyzer
> Acquisition of additional inputs such as thermo-couple, IEPE, counter, CAN, GPS, video, SCPI, etc.
> Up to 16 power phases (16 x U + 16 x I), expandable
> Redundant, integrated current transducer supply
> Various test bed integration possiblities
> Remote configuration and control

EVERY DEWETRON SYSTEM CAN BE A POWER ANALYZER

0.03 % Measurement error


10 MS per second/ per channel

>16 Power phases *expandable*






SMALLEST POWER ANALYZER



ALL-IN-ONE POWER ANALYZER



STATIONARY POWER ANALYZER



PORTABLE POWER ANALYZER

ADVANCED **POWER ANALYZER**







NEW

POWER ANALYZER	DEWE3-PA8	DEWE3-PA8-RM	DEWE3-A8-PA
Slots for TRION / TRION3 modules	8 TRION / TRION3 (up to 16 phases)		
High-speed channel expansion	Add TRIONet3 or OXYGEN-NET		
Low-speed channel expansion	XR modules		
Data storage	1 TB Solid State Disk dedicated for data storage		
Optional data storage	Upgrade from 1 TB to 2 TB industrial grade, PCIe attached Solid State Disk (SSD-PCIe-1T-2T)		
Gapless storing rate	Typ. 1 GB/s	Typ. 1 GB/s	Typ. 800 MB/s
Display	11.6“ multi-touch wide-screen, Full HD	No display	18.5“ multi-touch wide-screen, Full HD
POWER SUPPLY			
Input voltage (max.)	90 to 264 V_{AC}		
Sensor power supply	8 x (±15 V / +9 V)	8 x or 16 x (±15 V / +9 V)	8 x (±15 V / +9 V)
Integrated current transducer supply	Yes, with redundant supply		
DIMENSIONS			
Dimensions (W x D x H) without handle/feet	442 x 435 x 222 mm (5 u) (17.4 x 17.1 x 8.7 in.)	442 x 435 x 222 mm (5 u) (17.4 x 17.1 x 8.7 in.)	456 x 273 x 324.5 mm (18 x 10.8 x 12.8 in.)
Weight without modules and batteries	Typ. 14 kg (30.9 lb.)	Typ. 15.8 kg (34.8 lb.)	Typ. 15 kg (33 lb.)


Note: Please find the general chassis specifications for DEWE3-A4 on page 16 and PA-TRIONet3 on page 19.

INDIVIDUAL INPUT CONFIGURATION WITH SUB-MODULES


We offer you a unique modularity: 4 slots of each power module or even 8 slots of the TRION3-1810(M)-SUB-8 can be equipped with different sub-modules. Choose between direct current measurement modules or voltage modules to connect almost any kind of current or voltage transducer.

Create your individual input configurations with our sub-modules. They are user-exchangeable at any time and automatically detected. The calibration data is directly stored inside the sub-module.






TRION3-1810(M)-SUB-8



TRION(3)-18xx-POWER

	SUB-MODULE		RANGE	SAFETY	BANDWIDTH	CONNECTOR	USER-EXCHANGEABLE
VOLTAGE	1 V module		1 V_{RMS} (±2 V_{PEAK})	Not isolated. Depending on connected clamp	5 MHz	D-SUB-9 socket	Yes
	5 V modules		5 V_{RMS} (±10 V_{PEAK})		5 MHz	D-SUB-9 socket	
					100 kHz	D-SUB-9 socket	
	600 V module		600 V_{RMS} (±1500 V_{PEAK})	CAT II 600 V, isolated	300 kHz	Safety banana	
	XV module (seamless auto-range)		600 V_{RMS} (±1000 V_{PEAK}) 60 V_{RMS} (±100 V_{PEAK}) 6 V_{RMS} (±10 V_{PEAK}) 0.6 V_{RMS} (±1 V_{PEAK})		300 kHz	Safety banana	
CURRENT	Current transducer module		1 A_{RMS} (±2 A_{PEAK}) 0.5 A_{RMS} (±1 A_{PEAK}) 0.25 A_{RMS} (±0.5 A_{PEAK}) 0.1 A_{RMS} (±0.2 A_{PEAK})	Not isolated. Depending on connected clamp	5 MHz	D-SUB-9 socket	
	20 A module		20 A_{RMS} (±40 A_{PEAK})	CAT II 600 V, unfused	300 kHz	Safety banana (male)	
	2 A module		2 A_{RMS} (±4 A_{PEAK})				
	1 A module		1 A_{RMS} (±2 A_{PEAK})				
	0.2 A module		0.2 A_{RMS} (±0.4 A_{PEAK})				



FIXED HIGH-VOLTAGE INPUTS		RANGE	SAFETY	BANDWIDTH	CONNECTOR	USER-EXCHANGEABLE
Voltage input U1, U2, U3, U4		1000 V_{RMS} (±2000 V_{PEAK})	CAT IV 600 V / CAT III 1000 V	5 MHz	Safety banana	No



CURRENT TRANSDUCERS & CLAMPS




DEWETRON offers several solutions for current measurement from simple shunts to current clamps and high-precision zero flux transducers. There are versions for pure AC current which do not need any power supply and versions for DC and AC current which can be supplied from the DEWETRON instrument. Sensors requiring ±15 V or +9 V supply voltage can be powered directly. Therefore, sensors such as zero-flux transducers do not need an extra power supply.

LITE[PA] STANDARD POWER ANALYZER

The LITE[PA] is a high-precision Power Analyzer with 4 or 8 phases for easy test stand integration. The tried and tested input modules guarantee highly precise measurement results and offer the user enough flexibility to use all common current sensors.

> Most intuitive user interface for direct device operation, e.g. in laboratory use
> Effortless data connection to host systems for remote controlled test stand or end-of-line applications









INTERFACES

For easy data exchange, a variety of interfaces are offered. Inputs for speed and torque are available as standard and make the LITE[PA] suitable for testing electric motors.

> Sub-modules for all current sensors
  > Direct current up to 20 A_{RMS} (±40 A_{PEAK})

> 4 or 8 high-voltages up to ±2000 V_{PEAK}

> 8 x integrated current transducer supply

> Ethernet for remote control & data exchange
  > SCPI
  > XCP
  > UDP

> CAN
  > XR-TH8-S for temperatures
  > Data transfer to host system

> Digital I/O
  > Speed
  > Torque
  > Frequency

LITE[PA] SPECIFICATIONS	
POWER accuracy 0.5 Hz to 1000 Hz (1 year)	0.04%
Number of phases	4 to 8
Sampling rate	Up to 10 MS/s
Resolution	≤2 MS/s: 24-bit; >2 MS/s: 18-bit
Bandwidth	Up to 5 MHz
Temperature measurement	Via XR-series modules
Internal storage capacity	256 GB
Display	11.6" multi-touch wide-screen display, full HD
Data visualization	Freely configurable and arrangeable, multiple view screens
Advanced data processing	Formulas, filters, statistics, FFT, etc. (online and post processing)
Reporting	Integrated reporting, many export data formats (*.xlsx, *.mat, *.dat, *.csv., etc.)
Data sharing and offline analysis	Unlimited free VIEW licenses for workgroups (for multiple analysis PCs)
Host system data connection	CAN, Ethernet (SCPI, XCP, UDP)
Power supply	90 .. 264 V_{AC}
NEW **Integrated current transducer supply**	Yes, with independent power supply for sensors
Dimensions (W x D x H) without feet and handle	442 x 281 x 222 mm (17.4 x 11.1 x 8.7 in.); 5 u
Weight	4 ch: 9 kg (19.8 lb.); 8 ch: 9.5 kg (21 lb.)

DATA CONNECTION TO HOST SYSTEMS

The LITE[PA] is ready to be easily integrated into a wide variety of host systems. In addition to the CAN-bus, the data can also be transmitted via Ethernet, with various protocols such as SCPI or XCP. The remote control is usually done via SCPI; extensive commands are available to e.g. load predefined setups, make trigger settings, etc.



TEST STAND INTEGRATION



Leading test stand manufacturers rely on the measurement data from DEWETRON when it comes to reliable testing of important and critical components. Our various interfaces guarantee you a simple integration.

TEST STAND INTERFACES IN OXYGEN

Smart interface technology makes it easy to integrate DEWETRON power analyzers and measurement instruments into various test stand automation systems, such as PAtools® from NI. Depending on the system architecture of the test stand, DEWETRON systems are equipped with the right interface to ensure reliable data transmission, easy to use remote control and remote configuration, e.g. through TCP/IP-based protocols.

EtherCAT
INTERFACE

Typ. 100 ch
Typ. 500 S/s per channel

Data transfer & remote control

SCPI
OVER ETHERNET

Typ. 100 ch
Up to 10 kS/s per channel

Data transfer & advanced remote control

XCP
OVER ETHERNET

Typ. 20 ch
Up to 2 MS/s per channel

Interface to CANape and INCA

CAN
CAN-FD

Typ. 20 ch
Typ. 100 S/s per channel

DATA STREAM
OVER ETHERNET

Typ. >100 ch
Up to 2 MS/s per channel


DMD
READER

Libary to import recorded data
in 3rd party software

DEDICATED REAL-TIME POWER ANALYSIS SOLUTION

DEWETRON offers a dedicated solution for latency critical tests and applications to turn your DEWE3 system into a real-time Power Analyzer

- > Calculation of cycle-by-cycle power values
- > Data output interface: Ethernet UDP or EtherCAT slave
- > Data output rate: 1 kHz
- > Typical I/O latency: 2 ms (max: 4 ms)





ALL-IN-ONE SYSTEMS

> *Compact and flexible configuration*
> *Convenient for mobile applications with built-in display*
> *Powerful PC inside for fast online displays and analysis*









	DEWE3-A4	DEWE3-A4L	DEWE3-A8 / DEWE3-A12 NEW
Slots for TRION / TRION3 modules	4 TRION / TRION3	4 TRION / TRION3	8 or 12 TRION / TRION3
High-speed channel expansion	Add TRIONet3 or OXYGEN-NET		
Low-speed channel expansion	XR modules		
Data storage	1 TB SSD dedicated for data storage 512 GB SSD for operating system and application software		
Optional data storage	Up to 4 TB SSD	Up to 4 TB SSD	Up to 2 TB SSD
Gapless storing rate	Typ. 400 MB/s	Typ. 400 MB/s	DEWE3-A8: typ. 800 MB/s DEWE3-A12: typ. 1 GB/s
Display	13.3" multi-touch wide-screen display, Full HD	15.6" multi-touch wide-screen display, Full HD	18.5" multi-touch wide-screen display, Full HD
POWER SUPPLY			
Input voltage (max.)	10 to 36 V_{DC} isolated incl. external AC power supply	90 to 264 V_{AC}	90 to 264 V_{AC}
Option 1	Internal buffer battery for ~5 min operation	-	-
Option 2	External battery pack, 3 battery slots for ~1 h operation (DW3-UPS-DC)	-	-
DIMENSIONS			
Dimensions (W x D x H) without handle/feet	318 x 253 x 128 mm (12.5 x 10 x 5 in.)	462 x 320 x 135 mm (18.2 x 12.6 x 5.3 in.)	456 x 273 x 324.5 mm (18 x 10.8 x 12.8 in.)
Weight without modules and batteries [1]	Typ. 5.9 kg (13 lb.)	Typ. 8.5 kg (18.7 lb.)	Typ. 15 kg (33 lb.)

[1] Weight of one battery: 540 g (1.20 lb.)

OPTIONS AND ACCESSORIES



External battery pack: 250 W UPS with 3 battery slots
[DW3-UPS-DC]




Connection box to power eight current transducers
[DW2-CLAMP-DC-POWER-8]



Industrial USB 3.0 cameras for video input
[CAM-ALVIUM-x]

MAINFRAME SYSTEMS



> *Compact and flexible configuration*
> *Convenient for mobile applications*
> *Powerful PC inside for fast online displays and analysis*








	DEWE3-M4	DEWE3-M8s	DEWE3-M12s
Slots for TRION / TRION3 modules	4 TRION / TRION3	8 TRION / TRION3	12 TRION / TRION3
High-speed channel expansion	Add TRIONet3 or OXYGEN-NET		
Low-speed channel expansion	XR modules		
Data storage	1 TB SSD dedicated for data storage 512 GB SSD for operating system and application software		
Optional data storage	Up to 4 TB		
Gapless storing rate	Typ. 400 MB/s	Typ. 800 MB/s	Typ. 800 MB/s
POWER SUPPLY			
Input voltage (max.)	10 to 36 V_{DC} isolated; incl. external AC power supply	10 to 36 V_{DC} isolated; incl. external AC power supply; optional battery powered; 2 separate power inputs for mutual power supply backup	10 to 36 V_{DC} isolated; incl. external AC power supply; optional battery powered; 2 separate power inputs for mutual power supply backup
Option 1	Internal buffer battery for ~5 min. operation (DW2-PS-DC-Butter)	n/a	n/a
Option 2	External battery pack, 3 battery slots (DW3-UPS-DC)	n/a	n/a
DIMENSIONS			
Dimensions (W x D x H) without handle/feet	318 x 253 x 108 mm (12.5 x 10 x 4.3 in.)	339 x 281 x 239 mm (5 u) (13.3 x 11.1 x 9.4 in.)	461 x 281 x 239 mm (5 u) (18.1 x 11.1 x 9.4 in.)
Weight without modules and batteries [1]	Typ. 3.9 kg (8.6 lb.)	Typ. 9.1 kg (20.06 lb.)	Typ. 12 kg (26.46 lb.)

[1] Weight of one battery: 540 g (1.20 lb.)

OPTIONS AND ACCESSORIES



Box for connecting up to 4 GigE cameras; with integrated power supply
[CAM-GIGE-SPLIT-01-BOX]



Optional 10 GBit LAN interface available for
DEWE3-A4, DEWE3-M4 and DEWE3-RMx



Box for powering up to 8 current transducers
[DW2-CLAMP-DC-POWER-8]

RACK-MOUNT MAINFRAMES



> Rack-mount or benchtop data acquisition mainframe
> Silent cooling, easy to maintain fan slot
> Gapless storage of raw data up to 1 GB/s






	DEWE3-RM4	DEWE3-RM8	DEWE3-RM12	DEWE3-RM16
Slots for TRION / TRION3 modules	4 TRION / TRION3	8 TRION / TRION3	12 TRION / TRION3	16 TRION / TRION3
High-speed channel expansion	Add TRIONet3 or OXYGEN-NET			
Low-speed channel expansion	XR modules			
Data storage	1 TB high-speed PCIe Solid State Disk dedicated for data storage (removable) 512 GB SSD for operating system and application software			
Optional data storage	Upgrade from 1 TB to 2 TB industrial grade, PCIe attached Solid State Disk (SSD-PCIe-1T-2T)			
Gapless storing rate	Typ. 1 GB/s			
POWER SUPPLY				
Input voltage (max.)	90 to 264 V_{AC}			
DIMENSIONS				
Dimensions (W x D x H) without handle/feet	442 x 435 x 222 mm (5 u) (17.4 x 17.1 x 8.7 in.)			
Weight without modules	Typ. 15.8 kg (34.8 lb.)			

FRONT-END OPTION FOR MAINFRAME SYSTEMS

If your measurement system should not have a Windows operating system and no application software running on the system itself, we have the solution. We turn the mainframe chassis into a front-end system by installing our special Linux-based firmware. Applicable to DEWE3-M4/-M8s and all DEWE3-RMx mainframes.
Converted to front-ends, these chassis then connect to a separate host PC via LAN interface.
The standard interface is a 1 GBit Ethernet one. Optionally, a 10 GBit Ethernet interface is available for the DEWE3-RMx systems.




AIRCRAFT VERSION FOR FLIGHT TESTING

The DEWE3-RM12-AIRCRAFT is a special variant of the DEWE3-RM12, engineered for onboard power supply system testing in modern aircrafts.

Different from the standard version, it features a 24 V_{DC} power supply. Additionally, at the front are two vibration-resistant screw-lock RJ45 connectors for synchronization and Ethernet connection.





TRIONet3 FRONT-END

> *Up to 100 m distance between the TRIONet3 systems*
> *Gigabit LAN and USB3*
> *Distributable and stackable*

	TRIONet3
Slots for TRION / TRION3 modules [1]	2 TRION / TRION3
Low-speed channel expansion	XR modules (requires CAN input)
LAN	2 x 1000BASE-TX Gigabit Ethernet
LAN configuration	DHCP or Static IP
USB	USB 3.0
Synchronization	TRION-SYNC-BUS up to 100 m between nodes
System bandwidth	90 MB/s with one connected TRIONet3 (up to 50 MB/s with more than one)
Display	Status display with touch-screen
Cooling	2 temperature controlled ultra silent fans
HOST SYSTEM REQUIREMENTS	
Supported operating systems	Linux or Windows; 64-bit
Supported interfaces	USB 3.0; 1000BASE-TX Gigabit Ethernet
POWER SUPPLY	
Isolated power supply (max.)	10 to 32 V_{DC} (9 to 36 V_{DC})
Power consumption	Without modules 15 W, totally equipped max. 85 W
External power supply (included)	100 to 240 V ~50 to 60 Hz / 90 W
Option	Ext. battery pack, 3 battery slots for ~3 h operation (DW3-UPS-DC)
DIMENSIONS	
Dimensions (W x D x H)	320 x 205 x 55 mm (12.6 x 8 x 2.2 in.)
Weight without modules	Typ. 1.9 kg (4.2 lb.)
ENVIRONMENTAL SPECIFICATIONS	
Operating temperature	-20 °C to +60 °C (with pre-warmed unit)
Storage temperature	-20 to +70 °C
Humidity	10 to 90 % non cond., 5 to 95 % rel. humidity
Max. altitude	3000 m (9840 ft)
Sine vibration (EN 60068-2-6)	20 m/s²
Shock (EN 60028-2-27)	30 g
Random vibration (EN 60721-3-2)	Class 2M3


[1] Unsupported module: TRION-ARINC, TRION-MIL1553, TRION-EtherCAT-1-Slave

MOBILE WITH BATTERY PACK




TRIONet3 with DW3-UPS-DC battery pack for independed power supply

DISTRIBUTED APPLICATION



RUGGED & COMPACT NEX[DAQ]

NEX[DAQ] is the flexible "everyday tool" for all test and validation engineers and troubleshooters. Small, lightweight & very rugged: the 8-channel NEX[DAQ] with universal inputs and a great price-performance ratio.




IP 67

FANLESS

−20 °C TO +70 °C


INPUT SIGNALS



	NEX[DAQ]
Analog input	8 inputs for voltage up to ±100 V and full/half bridge, TEDS and MSI support
Further input types, via MSI	IEPE, quarter bridge, charge, RTD, LVDT, thermocouple, 0 to 20 mA, voltage up to ±600 V_{RMS}
Sampling rate	24-bit, 200 kS/s or 1 MS/s per channel
Accuracy	±0.05 % of reading, ±0.02 % of range ±50 µV
Hardware filter	Butterworth and Bessel, 2nd, 4th, 6th or 8th order
Sensor excitation	1 V to 24 V, freely programmable
Counters, digital I/O	4 advanced counters and 8 basic counters/digital inputs, 4 digital outputs
CAN-bus	2 interfaces for CAN2.0 and CAN-FD
Interface to host PC	USB-C or Ethernet
Power	9 to 36 V_{DC}
Power supply buffer	Buffered for 0.5 s in case of a voltage drop
Dimensions (W x D x H)	242 x 120 x 43.3 mm (9.52 x 4.72 x 1.7 in.)
Weight	1.25 kg (2.76 lb.)
Synchronization	Via Ethernet PTP/IEEE1588
Topology	Dasychain, Star


POWER SUPPLY OPTIONS

The NEX[DAQ] offers multiple power options for easy and worry-free use in any situation.



HIGHER CHANNEL COUNTS

Simply daisy-chain multiple rugged NEX[DAQ]s into a multi-channel system. A single cable is sufficient for data transfer and synchronization via Ethernet PTP/IEEE1588.




PURE RECORDING


PU[REC]

The PU[REC] is a portable and reliable data acquisition system for field tests, troubleshooting and maintenance in various application areas.











SPECIFICATION

- 16 measurement channels expandable via XR modules or MSI sensor interfaces
- 50 kS/s or 200 kS/s sampling rate
- Digital I/O and counter
- CAN (optional)
- Recording time of 168 h @ 50 kS/s or 42 h @ 200 kS/s
- Full-HD 15.6" multi-touch display
- Dimensions (W x D x H) 463 x 129 x 318 mm (18.2 x 5.1 x 12.5 in.)

SOFTWARE

- Analysis
- Visualization
- Post-processing
- FFT analysis
- Trigger & events
- Math & calculation
- Export features
- Reporting
- ...and many more

RECORDING

- Simple recording and storing of data
- Quick navigation on your PU[REC] or any PC with our OXYGEN measurement software
- Effortless data review also while still recording (DejaView)
- Various trigger conditions and powerful trigger actions
- Time-based & event-based file-split options
- Channel-specific storing options for waveform and statistics data recording
- Easy report and export features

RUGGED CHANNEL EXPANSIONS




Extend your measurement system with our low-speed channel expansions for temperature, voltage, current or resistance temperature measurements.

> Ruggedized measurement modules with integrated A/D conversion
> Extended operating temperature of -40 to +85 °C
> Fully isolated: channel to channel and channel to bus, power and chassis
> XR modules are extremely rugged and waterproof
> RS-485 or CAN interface (freely selectable with programmable interface)
> Sample rate: up to 200 Hz for CAN; up to 10 Hz for RS-485

XR MODULE		CHANNELS	INPUT RANGES	ISOLATION	SAMPLE RATE PER CHANNEL	IP RATING
XR-RTD8		8 isolated resistance temperature detector (RTD) inputs	Resistance: 0 to 5000 Ω RTD: Pt100, Pt200, Pt500, Pt1000, Pt2000	350 V_{DC}	CAN: 200 S/s RS-485: 10 S/s	IP 68 immersion depth 3 m
XR-TH8-S		8 isolated thermocouple inputs	Types K, J, T, R, S, N, E, L, C, U, B	1500 V_{AC}	CAN: 200 S/s RS-485: 10 S/s	n/a
XR-LA8		8 isolated current inputs	0 to 20 mA; ±20 mA; ±30 mA	350 V_{DC}	CAN: 200 S/s RS-485: 10 S/s	tbd.
XR-V8		8 isolated voltage inputs	Physical in. range: ±50 V Software selectable: ±100 mV, ±500 mV, ±1 V, ±2.5 V, ±5 V, ±10 V	350 V_{DC}	CAN: 200 S/s RS-485: 10 S/s	IP 68 immersion depth 3 m

STATIC EXPANSION

Add one or more ruggedized XR modules for more low-speed inputs. Interface is freely programmable as RS-485 or CAN interface.



MSI SENSOR ADAPTER



MSI (Modular Smart Interfaces) expand the functionality of TRION(3) and PU[REC] inputs.


> Automatically detected and set up
> Supported on TRION(3)-x-MULTI, TRION(3)-1802 and TRION(3)-1600 with TRION-X-dLV-CB16-D9 connector box

MODULAR SMART INTERFACES (MSI)	INPUT	SENSOR EXCITATION	BANDWIDTH (MAX.)	ACCURACY (TYP.)	SENSOR CONNECTION
MSI2-250R-20mA 	4 to 20 mA sensors	5 to 48 V AUX PWR	DC to 250 kHz [1]	±0.1 %	Miniature spring terminals
MSI2-STG 	Bridge type sensors Full-bridge, half-bridge, quarter bridge 120 Ω and 350 Ω	5 V and 10 V	60 kHz [1]	±0.1 %	Miniature spring terminals
MSI2-LVDT 	LVDT and RVDT sensors, 5- or 6-wire connection	3 V at 2.5, 5 or 18 kHz	1 kHz [1]	±0.1 %	Soldering pads
MSI-BR-ACC 	IEPE® sensors, typ. accelerometer, microphone	4 mA	1.4 Hz to 250 kHz [1]	±0.2 %	BNC
MSI2-CH-x 	Charge type sensors up to 100 000 pC	n/a	0.08 Hz to 250 kHz [1]	±0.5 %	BNC
MSI2-TH-x 	Thermocouple sensors; standard models for type K, J, T (others on request)	n/a	DC to 30 kHz [1]	±1 °C	Mini TC socket
MSI-BR-V-200 	Voltage up to ±200 V	n/a	DC to 100 kHz [1]	±0.1 %	BNC
MSI2-V-600 	Voltage up to 600 V_{RMS}	n/a	DC to 60 kHz [1]	DC to 1 kHz: ±0.1 % of reading ±100 mV >1 kHz to 5 kHz: ±0.5 % of reading ±100 mV >5 kHz to 10 kHz: ±1 % of reading ±100 mV	Safety banana
MSI-BR-RTD 	RTD sensors Pt100, Pt200, Pt500, Pt1000, Pt2000; 2, 3 & 4 wire connection	1.25 mA	DC to 10 kHz [1]	±0.1 %	Binder 712 series 5-pin socket

[1] Consider limit of used TRION(3) module

MSI CONNECTOR BOX

The MSI connector box TRION-X-dLV-CB16-D9 is a feature expansion box for TRION(3)-1802-dLV-32 and TRION(3)-1600-dLV-32 modules by MSI (Modular Smart Interfaces) support. This connector box enables measurement of strain gauge and bridge sensors, IEPE®, LVDT and RVDT, thermocouple, charge, RTD and voltage up to 600 V_{RMS}.




NO LIMITATIONS WITH SYNCHRONIZED SYSTEMS

If you need more than one DAQ system, even on different locations, we have several networking solutions for you.

OXYGEN-NET

The OXYGEN-NET software option makes it possible to combine multiple devices to one virtual measurement device.
> Easy-to-use synchronized measurement for hundreds of input channels from 10 S/s to 10 MS/s per channel
> Works with absolute time synchronization (PTP, IRIG, GPS) as well as with the built-in TRION-SYNC-BUS
> Remote and local data storage possible for redundancy
> Setup and control of all nodes from the main device

SYNC for **100s** of channels




EXPANSION FOR MORE CHANNELS

You need more channels for your DAQ system? No problem! Expand your system via front-ends or XR modules, depending on the necessary speed.


FRONT-END EXPANSION

Add one or more TRIONet3 front-end chassis for more channels and high-speed expansion. Up to 100 m between units possible.



STATIC EXPANSION

Add one or more rugged and waterproof XR modules via CAN or RS-485 interface




SYNCHRONIZATION POSSIBILITIES

Synchronization of multiple systems ensures perfectly synchronized measurements without any time shifts between the systems and therefore guarantees highest data quality. DEWETRON offers various synchronization possibilities to have the ideal solution for every application. Different sync sources can be used such as GPS, PTP, gPTP, IRIG or PPS.

NEW

PTP-SYNC / gPTP-SYNC


Various instruments from DEWETRON or 3rd party instruments can be synchronized via PTP (Precision Time Protocol) and gPTP (Generalized Precision Time Protocol). Data transmission via Ethernet and local data storage possible.



GPS-SYNC

Two or more instruments synchronized via GPS.
Most systems are equipped with GPS-interface directly on the front panel. For others, you need the TRION-VGPS-V3 module.


Data transmission via Ethernet and local data storage possible.



IRIG-SYNC

Use your DEWETRON chassis as an IRIG (InterRange Instrumentation Group) master to output an IRIG B DC signal for synchronization via three possibilities:

> Directly at the front panel (depending on the chassis)
> TRION-TIMING-V3
> TRION-VGPS-V3



ANALOG SIGNAL CONDITIONING

Chassis for isolated signal conditioning amplifiers, suitable for a wide variety of sensors.





	DEWE-30-16	DEWE-30-32
Slots for DAQP modules	16	32
Interfaces	RS-232, RS-485, XR	
Conditioned signal output	±5 V (±10 V as option), buffered	
Output connector standard	D-SUB-37	
Output optional	BNC	
Power supply	100 to 240 V_{AC}	
Optional power supply	10 to 32 V_{DC}	
Dimensions	438.5 x 253 x 133 (17.3 x 10 x 5.2 in.)	438.5 x 253 x 253 mm (17.3 x 10 x 9.6 in.)
Weight (depending on configuration)	4.5 kg (9.9 lb.)	7 kg (15.4 lb.)
ENVIRONMENTAL SPECIFICATIONS		
Operating temperature	0 to +60 °C	
Storage temperature	-20 to +70 °C	
Humidity	10 to 90 % non cond., 5 to 95 % rel. humidity	
Vibration	EN 60068-2-6, EN 60721-3-2 class 2M2	
Shock	EN 60068-2-27	

UNIVERSAL ANALOG MEASUREMENT

UNIVERSAL ANALOG MODULE	FEATURES	BANDWIDTH	ISOLATION	CONNECTOR TYPE
 **DAQP-STG** 	Auto sensor balance Internal completion for ½ and ¼ bridge µV amplifier with high bandwidth Continuously variable gain from 0.5 to 10 000	300 kHz	350 V_{DC}	D-SUB

COMBINATION WITH TRION(3)/DEWE3-SYSTEMS

Use the TRION(3)-1802-dLV or TRION(3)-1600-dLV as input modules for the conditioned analog signals.



DEWE-30-16

DEWE3-M4 with TRION-1802-dLV module

OXYGEN MEASUREMENT SOFTWARE

With the OXYGEN all-in-one software, the data acquisition, recording, calculation, visualization and analysis has never been easier. Use only one software for all applications. Also for 3rd party components.

Windows Linux

We are the only manufacturer of measurement technology to offer you the advantage of choosing between Windows and Linux.



DATA ACQUISITION

Synchronous and continuous acquisition of data from several sources: analog, digital, encoder, counter, CAN, SCPI, Ethernet, video, GPS and many more.


> Analog data with up to 10 MS/s
> Digital and encoder data with automatic RPM and angle calculation
> CAN(-FD) decoding via *.dbc including J1939 Compatible with Vector VN-series
> Ethernet receiver for external sensors (opt.)
> Video data from USB or GigE-camera
> Precision GPS position data via TRION3, GeneSys ADMA or OxTS RT series
> Plugin to request and decode OBD2 parameters



RECORDING

Store all your acquired data in one data file with a simple touch on the record button. You can achieve data rates of up to 1 GB/s and you never have to worry about loosing any data. Furthermore, review your data during recording with the DejaView function.


> File-split option for generating a new file after an amount of time or event occurrence
> Channel-wise sample rate selection
> Channel-specific storing options for waveform and statistics data recording
> Adjustable playback speed from 1/1000x to 1000x



ANALYSIS AND POST-PROCESSING

The real work often begins after the live measurement. To complete this workflow, OXYGEN also supports post-processing and analysis of the recorded data.

> Use many of the math and calculation (also incl. FFT) features to refine your measurement results
> Create new visualizations and measurement screens
> Quickly navigate through the data with well-known gestures and intuitive zoom and scrolling mechanisms
> Export data to complete your workflow




For post-processing, you do NOT need an OXYGEN license

REPORTING

Use OXYGEN for your whole measurement work-flow. From acquiring data to post-processing and finally reporting the data.


> Create separate reporting pages (in addition to the measurment screens) with typical printing layouts
> Duplicate a measurement screen or create new pages with a simple click
> Use all instruments and visualizations also in the reporting pages
> Separate time-cursor on each page available to report different time snippets in one report
> Directly print or save to pdf
> Export your measurement to a video



EXPORT


If you need to use another analysis software for further data processing, we offer data export for the most common applications and formats.

> Universal formats: CSV and TXT with selectable delimiter and timestamp format
> Advanced formats: Excel, MATLAB, ASAM MDF4, DIAdem, DSPCon, DynaWorks, IMC Famos 2, HDF5, MTS RPC III, NetCFD, NI TDMS, Universal File Format 58, Wave
> Select channels and/or time-range of the exported data
> Optional automatic export at measurement end



MATH AND CALCULATION


> FORMULA: For arithmetic and more advanced calculations (trigonometric, logical and measurement functions)
> STATISTIC: Block-wise, Triggered and Overall-statistics to calculate statistic values, e.g. AVG, RMS, MIN and MAX, PP...
> FILTER High, low, bandpass and bandstop IIR-filter and FIR-filter up to the 10th order
> DMS-ROSETTE calculation module for 45°, 60°, and 90° setups
> PSOPHOMETRIC ANALYSIS for railway and telecommunication applications
> FFT spectra overlap, peak hold and pin extraction
> INTEGRATION / DERIVATION with optional signal filter



TRIGGER & EVENTS

The powerful trigger and event system makes it easy for you to record data in case of events, create markers, set a digital output or make a snapshot of the actual measured data. Create different events, each consisting of one or more trigger conditions and one or more actions.

> Many different trigger conditions: signal level (positive/negative edge, window) with optional rearm level, keyboard or time
> Powerful actions like start/stop of recording, set an alarm with optional digital output, set a marker with pre-defined text or make a snapshot of the actual measured data.



VIDEO INPUT

Cameras are implemented as additional sensors in OXYGEN, so you really get the "complete picture" of your measurement task.
Applications start with very simple video documentation (measurement setup, weather, environment, etc.) with a cheap webcam and extend to really complex tasks with up to 8 cameras, whose individual frames are perfectly synchronized with all other data (e.g. analog, CAN, counters, GPS...).


> USB webcams
> Synchronized USB and GigE cams, up to 289 fps
> High-speed cams, up to 100.000 fps (post sync)



OXYGEN-NET

Many applications require more than one measurement device, sometimes even at different locations. OXYGEN-NET makes it possible, to sum up all devices to one virtual measurement device. You only need a reliable network connection, and you can simply claim all available nodes and operate it from the main device.

> Create one big virtual device with several remote nodes (measurement cloud)
> No complicated settings needed, simply claim and remove nodes with one click
> Works with absolute time synchronization as well as with TRION-SYNC-BUS
> Remote and local data storage possible for redundancy
> Multiple Master clients and redundant Master clients supported



SOUND LEVEL

The sound level plugin provides online determination of the time-dependent sound pressure level, the energy equivalent sound pressure level, freely definable statistical sound pressure levels and many more. This plugin turns your DEWETRON device into the ideal solution for analyzing the acoustical emission of machines, for determining the spatial and statistical sound pressure level distribution in buildings and for long-term noise monitoring.


> A-, B-, C-, D- and Z-frequency weighting (according to DIN EN 61672-1)
> Fast, slow and impulse time weighting (according to IEC 651)
> Reference level for air (20 µPa) and water (1 µPa)
> Overall and interval logging
> Audio replay feature



FFT ANALYSIS

Experience top-tier frequency domain analysis with OXYGEN's flexible and user-friendly FFT Analysis. Benefit from powerful instruments and math calculations to tackle any task:


> Freely selectable (not only 2N) number of input samples or line resolution.
> Optional zero-padding for enhanced line resolution.
> Various windowing and scaling types selectable.
> Reference curves to visualize thresholds and warnings in the frequency domain.
> STFT to visualize spectral changes in time.
> Various 2- and 3-dimensional visualization and analysis options.



MODAL TEST

With OXYGEN's Modal Test option you can analyze the frequency characteristics of a mechanical structure to determine resonances, damping characteristics and more.


> DUT excitement via modal hammer
> SISO & SIMO tests with moving hammer and moving sensor
> Calculation of
  > Complex transfer function
  > Coherence of several hits
  > Mode indicator function
> Various interactive visualization options
> Data export into *.uff and other formats for post processing
> Modal shape animation
> SDOF circle fit



ORDER ANALYSIS

The noise and vibration analysis module for rotating machines turns your OXYGEN into a full order analysis instrument for calculation and visualization of frequency and order spectra vs. speed.


> Simultaneous frequency and order domain analysis
> Smart resampling algorithm for accurate and fast results
> Selectable speed ranges from 60 RPM to 100 000 RPM
> Order resolution from 0.01 to 1, with up to 90 % overlapping
> Order extraction for selected orders for use in recorder or XY-instrument
> Visualization of the resulting matrix in intensity diagrams
> Visualization of extracted orders in Orbit Plot and Polar Plot



EFFICIENCY MAPS

The matrix sampler is the solution for visualizing the efficiency of your electric drivetrain at different load steps or running speeds online. Create the calculation module directly in your power group. The efficiency map of the drivetrain will be filled up during the measurement.


> Possibility to refill single measurement points without overwriting the whole matrix
> Easy-to-use and intuitive operation
> Several trigger options to fill the map with data
> Freely definable matrix size
> Assignment of any channel to X-, Y- and Z-axes for visualizing any 3-dimensional signal dependencies



POWER ANALYSIS

Turn your DEWETRON measurement device into a fully-featured power analyzer:

> Analysis of 1–9 phase power systems (1P2W, 2V2A, 3P3W, 3P4W, 2x 3P3W, ...)
> Several power systems are logically summarized into power groups
> Gapless cycle-by-cycle calc. no blind spots
> Unique fundamental frequency detection with delay compensation for highest accuracy and reliability
> BASIC: vol., curr., RMS, AVG, fundamental & symmetrical components, active/reactive/apparent power total & fundamental, energy
> ADVANCED: harmonics (IEC 61000-4-7), flicker (IEC 61000-4-15), flicker emission (IEC 61400-21) and mechanical power/efficiency
> EXPERT: rolling calculation meets FGW-TG3



SDK FOR PROGRAMMERS

With DEWETRON, you get an open platform to develop your own measurement application or extension. Depending on your requirements, you can choose between two Software Development Kits: OXYGEN-SDK and TRION-SDK.

OXYGEN SDK

With OXYGEN SDK, you are capable of developing your own plugins for the OXYGEN measurement software.

AVAILABLE FEATURES FOR THE PLUGIN

> Advanced calculations and data processing
> 3rd party data output
> Data output
> Special export formats
> Read and write data from/to numeric channels
> Create new channels
> Create config items for setup save/load and user config
  > Numeric, text, channel list
> Integration of video sources

This and much more allows you, to extend OXYGEN with additional calculations and data I/O.

AVAILABLE FUNCTIONALITY

> Custom QML-GUI for add channel dialog for easy user setup
> Custom QML-GUI for data export and special options
> User configuration elements
  > Text and number inputs for all kinds of configuration
  > Combo boxes (drop-down & custom input)
  > File picker for selecting files
> Read data from any OXYGEN channel
> Create new OXYGEN channels and write data into

EXAMPLE PLUGIN FUNCTIONALITIES

> Easy setup of the MS Visual Studio environment with SDK wizard
> XR plugin
> OBD2 plugin
> Frequency measurement
NEW > Camera integration

SPECIAL DATA SINKS


> Ethernet sender

SPECIAL EXPORTER

> Dynaworks
> DIAdem

SPECIAL DATA SOURCES

> SCPI query plugin
> AK dyno plugin
> Serial CSV reader
> Modbus TCP/IP




If OXYGEN does not provide a certain function, create it on your own

Get started and visit
https://github.com/DEWETRON/OXYGEN-SDK

TRION SDK

The TRION SDK helps you to build your own measurement application based on the DEWE3 and TRION/TRION3 hardware platforms. It also supports the use of TRIONet.
We support Windows 10 (64-bit), Ubuntu, and Redhat/CentOS Enterprise Linux.
C/C++ are the natively supported programming languages, additional bindings to Python, C# and Delphi.



1

OXYGEN SCPI VI

Use the OXYGEN SCPI interface to transfer data into LabVIEW™ during data acquisition and recording in OXYGEN. Various channels like analog, math or power group channels are supported. The channel setup and configuration is done in OXYGEN and the data can be stored redundantly in OXYGEN and LabVIEW™.

SCOPE OF SUPPLY

> OXYGEN's SCPI interface for data transfer and configuration
> LabVIEW™ VI including the required SCPI commands
> Documentation included in LabVIEW™ code
> Quick start programming example
> Maximum data transfer rate: 10 kS/s
> Typical number of channels to be transferred: 100 channels

WHEN TO USE

> Channels calculated in OXYGEN (such as power groups) shall be transferred into LabVIEW™
> Integration of DEWETRON data acquisition system into a LabVIEW™ based test bed
> No LabVIEW™ based hardware configuration required

NOTE:
Requires LabVIEW™ on the data acquisition system or on a separate PC that is connected to the same Ethernet network as the data acquisition system.

NI LabV
INTEGR

FOUR SOLUTIONS TO S
YOUR MEASUREMENT

2

LABVIEW™ DRIVER FOR TRION(3)


Use the hardware driver to gather data from the TRION API, which is in direct communication with LabVIEW™ . TRION and TRION3 modules in any chassis are supported. The hardware and channel configuration is done in LabVIEW™.

SCOPE OF SUPPLY

> User friendly encapsulation of the device functions into VIs
> Possibility to acquire the measurement data from the TRION boards in LabVIEW™ with just a few VIs
> Dedicated VIs for channel configuration
> Documentation included in LabVIEW™ code
> Quick start programming examples included

WHEN TO USE

> For customized software solutions developed in LabVIEW™
> When TRION hardware shall be used in parallel with 3rd party hardware in LabVIEW™
> For solutions requiring regulation and automation based on LabVIEW™



NOTE:
Requires LabVIEW™ installed on the data acquisition system (or on the host PC in case TRIONet3 is used)

Please note: NI and LabVIEW are trademarks of National Instruments Corporation (NI). Neither DEWETRON, nor any goods or services offered by DEWETRON, are affiliated with, endorsed by, or sponsored by Emerson or NI.

OXYGEN DATASTREAM VI

3

Use the OXYGEN DataStream interface to transfer data into LabVIEW™ during data acquisition and recording in OXYGEN. Various channels like analog, math or power group channels are supported. The channel setup and configuration is done in OXYGEN and the data can be stored redundantly in OXYGEN and LabVIEW™.

SCOPE OF SUPPLY

> OXYGEN's SCPI interface for data transfer and configuration
> LabVIEW™ VI including the required SCPI commands
> Documentation included in LabVIEW™ code
> Quick start programming example
> Maximum data transfer rate: native channel sample rate
> Typical number of channels to be transferred: 100 channels à 100 kS/s

WHEN TO USE

> Channels calculated in OXYGEN (such as power groups) shall be transferred into LabVIEW™
> Integration of DEWETRON data acquisition system into a LabVIEW™ based test bed
> No LabVIEW™ based hardware configuration required

NOTE:
Requires LabVIEW™ on the data acquisition system or on a separate PC that is connected to the same Ethernet network as the data acquisiton system.

VIEW™
RATION

EAMLESSLY INTEGRATE
T DATA INTO LabVIEW™

OXYGEN *.TDMS-EXPORT

4


Export your OXYGEN *.dmd data files directly into the *.tdms format to open the files in LabVIEW™. Different export options are available (export all or only specific channels, entire data or only specific time span...).

SCOPE OF SUPPLY

> Standard OXYGEN *.tdms export

WHEN TO USE


> Direct export into the LabVIEW™ format
> Easy integration of data into LabVIEW™
> No configuration required



NOTE: Requires LabVIEW™ on an arbitrary PC that is used for data post processing.

CUSTOMER CARE CENTER

Choosing DEWETRON means choosing a partner that accompanies you along the entire way. With the purchase of your DEWETRON system, you benefit immediately from the instant access to our global network of professional support, service and various training offers.



CONTACT OUR SUPPORT TEAM

us.customercare@dewetron.com

+1-401-398-2735

SEND IN YOUR SYSTEM

For calibration, maintenance and repair issues fill out this form ccc.dewetron.com/rma

FOLLOW US ON LinkedIn

Follow us on LinkedIn and you will never miss any DEWETRON update.







CALIBRATION SERVICES

The accuracy of your DEWETRON data acquisition system is paramount. Thus, all DEWETRON systems are of course calibrated before delivery. By calibrating your DAQ system annually, you can ensure the continued integrity of your measurement data.

DEWETRON offers two types of calibration:
- > NIST standard factory calibration
- > Accredited calibration according to ISO 17025



ACCREDITED SCOPE

V 1000 DC	**VOLTAGE (DC)**
V 1000 AC	**VOLTAGE (AC)**
I 20 DC	**CURRENT (DC)**
I 20 AC	**CURRENT (AC)**
P 20 k DC	**POWER (DC)**
P 20 k AC	**ACTIVE POWER (AC)** up to 850 Hz fundamental frequency
K, J, T	**TEMPERATURE SIMULATION (DC)**
Pt100 Pt200 Pt500 Pt1000	**TEMPERATURE SIMULATION (RTD)**
1 M DC	**RESISTANCE (DC)**

POWER CALIBRATION

Especially for your power (analyzer) measurement we offer:
- > Calibration of power values (voltage and current applied simultaneously)
- > From power-factor 1 down to 0.1
- > Up to 850 Hz fundamental frequency

Download our detailed CMCs

ccc.dewetron.com/dl/Scope_of_Accreditation


WARRANTY EXTENSION

UP TO 5 YEARS

Generally, all DEWETRON hardware components are covered by a limited one-year warranty covering parts and labor on a depot basis. This standard warranty may be extended to include up to four additional years of assurance.
The premise for the **warranty extension up to 5 years**[*)] is the annual calibration and maintenance of your DAQ system by the professionals at the DEWETRON factory.

*) Please check out our terms and conditions for further details.

OUR WARRANTY EXTENSION COVERS FOLLOWING PARTS

CHASSIS		PC hardware (SSD, mainboard)	✓
		Power supply	✓
		DAQ components	✓
MODULES		TRION modules	✓
		Sub-modules	✓
		XR modules	✓








ELECTRICAL POWER & NVH

IN COOPERATION WITH MÜLLER-BBM VibroAkustik Systeme

> Optimization of NVH (Noise, Vibration and Harshness) & e-power performance through motor control during testing
> Target-based development of active components on the test bench
> Correlation analysis between NVH & e-power data for an all-encompassing engineering approach
> Combination of NVH & e-power data from several sources in only one view
> Overall e-NVH system analysis with PTP synchronized measurement data



YOUR ADVANTAGES

> Online data analysis with the processing of NVH & e-power signals in PAK
> Seamless integration of DEWETRON's power analyzer into the PAK family
> Optimization of NVH & e-power performance through motor control on test benches
> Usage of the proven MBBM-VAS rotating machinery software packages
> Online simulation of vehicle response on test benches using blocked force methodology
> PTP synchronized data acquisition
> 10 MS/s & continuous raw data storage for PWM signals with DEWETRON's OXYGEN

DEWETRON + OXYGEN

> Dedicated power analysis of systems with up to 9 phases with various power parameters
> Highest flexibility due to a modular design & DEWETRON's mixed signal inputs approach
> Perfect signal synchronization to guarantee the most reliable measurement data integrity
> Highly dynamic range with tremendous accuracy as a key requirement for test bench applications
> Continuous & gapless storage of raw data
> Integrated (redundant) sensor supply for a direct connection to the power analyzer

MBBM-VAS + PAK

> Open architecture combining data streams from different sources by a live IO hub
> NVH software suite with dedicated e-NVH analyses, including Clarke/Park transformation, PWM orders & sound design
> Direct visualization of acquired quantities & spectral evaluations in the powerful reporting tool (highly interactive graphic functionalities)
> The perfect solution for troubleshooting, highly standardized tasks, quality assurance, mobile measurements & test bench operation

ACCESSORIES



CURRENT TRANSDUCERS

We provide several solutions for current measurement: from simple shunts to current clamps and high-precision zero flux transducers. All transducers can be supplied from the DEWETRON instrument.



CURRENT TRANSDUCER SUPPLY

We offer a current transducer box to power up to 8 current transducers directly from your DEWETRON DAQ system



POWER SUPPLY


For mobile applications we provide a battery charger and system power supply with 3 hot-swappable batteries.



TRANSPORTATION

We offer special sturdy carrying cases for the safe transport of all our measurement systems.

VIDEO CAMERAS



HIGH SPEED CAMERAS
UP TO 100,000 FPS

> Independent from HS camera system
> Can be added to every DEWETRON system
> Measurement screen can be exported as video report
> Analysis can be done on every computer

USB / ETHERNET CAMERAS
UP TO 289 FPS

Rugged and lightweight ALVIUM industrial cameras with high image quality with up to 289 fps. Several models with different resolution and USB 3.0 or GigE connection.















ABOUT DEWETRON

DEWETRON is a manufacturer of precision test and measurement systems and part of the globally operating Anritsu Group. Our reliable measurement data help customers worldwide make processes more predictable, efficient, and safer.

Our strength lies in customized measurement solutions: ready to use right away while remaining flexible to adapt to dynamic testing requirements in the energy, automotive, transportation, and aerospace industries.

More than 35 years of experience and innovation have made DEWETRON a trusted partner in the global test and measurement market.

More than 25,000 DEWETRON measurement systems and over 400,000 measurement channels are in continuous use at leading companies worldwide.

DEWETRON's quality is certified according to ISO 9001 and ISO 14001.
The high integrity of the measurement data is guaranteed by our own accredited calibration lab according to ISO 17025.

THE MEASURABLE DIFFERENCE.

Get to know our
GLOBAL OFFICES

DEWETRON

DEWETRON Inc.
2850 South County Trail
East Greenwich, RI 02818
USA

+1-401-284-3750
us.sales@dewetron.com
www.dewetron.com

B230101US • All trademarks are acknowledged to be the property of their owners. Specification subject to change without notice. Printed in the USA. © DEWETRON GmbH 09/2026